



JOHN DEERE

2009

**MODEL
COMPARISON**



ADTS

BACKHOE LOADERS

CRAWLER DOZERS

CRAWLER LOADERS

COMPACT EXCAVATORS

EXCAVATORS

LOADERS

LANDSCAPE LOADERS

MOTOR GRADERS

SKID STEERS

COMPACT TRACK
LOADERS

SCRAPER SPECIAL
TRACTORS

CARRY-ALL AND
EJECTOR SCRAPERS

COMPACT UTILITY
TRACTORS

GATOR™ UTILITY
VEHICLES

2009 MODEL COMPARISON

MOTOR GRADERS

		Weight with Front Push Block and Ripper				
DEERE	HP			CAT	VOLVO	KOMATSU
Tandem Drive:						
670G	185	40,930 lb.		12M VHP	G930	GD555-3 VHP
770G	230	41,350 lb.		140M VHP	G930, G940	GD655-3 VHP
870G	255	42,270 lb.		160M VHP	G960, G970	GD675-3 VHP
6WD:						
672G	195	42,740 lb.		—	—	—
772G	245	43,170 lb.		140M AWD	G946	—
872G	275	44,220 lb.		160M AWD	G946, G976	—

EXCAVATORS

DEERE	Max. Digging Depth	Operating Weight	Transport Width	CAT	HITACHI	VOLVO	KOMATSU
75D	13 ft. 6 in.	17,743 lb.	8 ft. 1 in. (24)	308D CR	ZX75US-3	ECR88	PC78US-6
85D	13 ft.	18,821 lb.	8 ft. 1 in. (24)	308D CR SB	ZX85USB-3	—	PC88MR-8
120D	19 ft. 11 in.	28,498–30,702 lb.	8 ft. 10 in. (28)	312D	ZX120-3	EC140C LC	PC130-8
135D	19 ft. 9 in.	31,147–32,747 lb.	8 ft. 10 in. (28)	314C CR	ZX135US-3	ECR145CL	PC138USLC-8
160D LC	21 ft. 4 in.	39,980 lb.	8 ft. 10 in. (28)	315D L	ZX160LC-3	EC160C LC	PC160LC-7
190D W (Wheeled)	19 ft. 2 in.–19 ft. 5 in.	43,211–45,636 lb.	8 ft. 4 in.	M318D	ZX190W-3	EW180C	—
200D LC	21 ft. 11 in.	49,940 lb.	10 ft. 6 in. (32)	320D L	ZX200LC-3	EC210C LC	PC200LC-8
220D W (Wheeled)	19 ft. 11 in.–20 ft. 8 in.	49,207–52,003 lb.	8 ft. 4 in.	M322D	ZX220W-3	EW210C	—
225D LC	22 ft.	53,936 lb.	10 ft. 6 in. (32)	321D LCR	ZX225USLC-3	ERC235CL	PC228USLC-3
240D LC	24 ft. 7 in.	54,654 lb.	11 ft. 1 in. (32)	324D L	ZX240LC-3	EC240C LC	PC220LC-8
270D LC	25 ft. 11 in.	63,425 lb.	11 ft. 1 in. (32)	325D L	ZX270LC-3	EC290C LC	PC270LC-8
350D LC	26 ft. 10 in.	77,970 lb.	11 ft. 1 in. (32)	330D L	ZX350LC-3	EC330C LC	PC300LC-8
450D LC	27 ft. 2 in.	106,180 lb.	10 ft. 10 in. (36)	345D L	ZX450LC-3	EC460C LC	PC400LC-8
650D LC	30 ft.	152,192 lb.	12 ft. 3 in. (36)	365C L	ZX650LC-3	EC700C LC	PC600LC-8
850D LC	31 ft. 5 in.	185,876 lb.	12 ft. 3 in. (36)	385C L	ZX850LC-3	—	PC800LC-8

COMPACT EXCAVATORS

DEERE	Max. Digging Depth	Operating Weight	Transport Width	BOBCAT	CAT	KOMATSU	KUBOTA	TAKEUCHI
17D	7 ft. 1 in.	4,173 lb.	4 ft. 2 in.	323	301.8C	PC18MR-3	U15	TB016
27D	8 ft. 6 in.	6,358 lb.	5 ft. 1 in.	425	302.5C	PC27MR-3	U25	TB228
35D	10 ft.	7,760 lb.	5 ft. 9 in.	430	303C CR	PC35MR-3	U35	TB235
50D	11 ft. 8 in.	10,811 lb.	6 ft. 7 in.	435	304C CR	PC45MR-3	U45	TB250
60D	12 ft. 4 in.	13,653 lb.	6 ft. 7 in.	337	305C CR	PC55MR-3	KX-161	TB153FR

WHEEL LOADERS

DEERE	Bucket Capacity	Loader Dump Clearance	CASE	CAT	VOLVO	KOMATSU
244J	1.0–1.4 cu. yd.	8 ft. 4.4 in. (1.0)	221E	906H	L25B	WA-70-5, WA-80-5
304J	1.4 cu. yd.	8 ft. 9 in.	321E	908H	L30B, L35B	WA-100M-5
344J	2.0 cu. yd.	9 ft. 4 in.	—	914G	L40B, L45B	WA-150-5
444K	2.5 cu. yd.	8 ft. 9 in.	521E	924H, 924Hz	L50E, L60F	WA-200-6
524K	2.75 cu. yd.	9 ft. 1 in.	521E	924H, 924Hz	L60F	WA-200-6, WA-250-6
544K	3.0 cu. yd.	9 ft. 3 in.	621E	928Hz, 930H	L70F	WA-250-6
624K	3.5 cu. yd.	9 ft. 5 in.	721E	938H	L90F	WA-320-6
644K	4.25 cu. yd.	9 ft. 4 in.	821E	950H	L110F	WA-380-6
724K	4.25–4.75 cu. yd.	9 ft. 2 in. (4.75)	—	962H	L120F	WA-430-6
744K	5.25–5.75 cu. yd.	10 ft. (5.25)	921E	966H	L150F	WA-450-6
824K	6.0–6.75 cu. yd.	10 ft. 6 in. (6.0)	—	972H	L180F	WA-480-6
844K	6.25–8.1 cu. yd.	10 ft. 11 in. (7.25)	1221E	980H	L220F	WA-500-6

TOOL CARRIERS/PARALLEL LIFT

DEERE	Bucket Capacity	Loader Dump Clearance	CASE	CAT	VOLVO	KOMATSU
444K Powerlifel™	2.0–2.5 cu. yd.	8 ft. 4 in. (2.5)	521EXT	924H	L50E, L60F	WA-200PZ-6
544K Powerlifel	2.5–3.0 cu. yd.	8 ft. 9 in. (3.0)	621EXT	930H	L70F	WA-250PZ-6
624K Powerlifel	3.0–3.5 cu. yd.	8 ft. 11 in. (3.5)	721EXT	IT38H	L90F	—
644K Powerlifel	4.0 cu. yd.	8 ft. 9 in.	—	—	—	—

BACKHOES

DEERE	Digging Depth		Loader Dump Clearance	Operating Weight	CASE				KUBOTA
	Standard	Extendable			(All units are Series 3)	CAT	NEW HOLLAND	JCB	
110 TLB	9 ft. 10 in.	NA	7 ft. 4 in.	7,600 lb.	—	—	—	1CX	L39/L48
310J	14 ft. 3 in.	17 ft. 11 in.	8 ft. 10 in.	13,880 lb.	580M	416E	—	3C 14 ft.	—
310SJ	14 ft. 6 in.	18 ft. 5 in.	8 ft. 10 in.	14,510 lb.	580SM, 580SM+	420E/IT	B90B, B95B, B95BLR, B95BTC	3CX 14 ft., 4CX 14 ft.	—
310SJ TMC	14 ft. 11 in.	18 ft. 5 in.	8 ft. 10 in.	18,017 lb.	—	—	—	—	—
315SJ	14 ft. 6 in.	18 ft.	8 ft. 10 in.	18,600 lb.	—	—	—	—	—
410J	15 ft. 10 in.	20 ft.	8 ft. 4 in.	15,080 lb.	590SM, 590SM+	430E/IT	B110B, B115B	3C 15 ft., 3CX 15 ft., 4CX 15 ft.	—
410J TMC	16 ft. 1 in.	20 ft.	8 ft. 4 in.	19,022 lb.	—	—	—	—	—
710J	17 ft. 10 in.	22 ft. 4 in.	9 ft. 7 in.	23,000 lb.	—	450E	—	3CX 17 ft., 4CX 17 ft.	—

LANDSCAPE LOADERS

DEERE	Operating Weight	Loader Dump Clearance	Loader Bucket Capacity	CASE	NEW HOLLAND	JCB	KUBOTA	CAT
110 TLB	5,740 lb. (less box)	7 ft. 4 in.	0.6 cu. yd.	—	—	—	L35, L48, M59	—
210LJ	9,130 lb.	8 ft. 9 in.	1.00–1.12 cu. yd.	570M XT	U80	3C LL	—	414E IL

DOZERS

DEERE	Operating Weight	Blade Width	HP	CASE	CAT	KOMATSU
450J LT/LGP	16,283–17,525 lb.	97–124 in.	77	650K Series 3	D3K/LGP	D31EX-21/D31PX-21
550J LT/LGP	17,016–18,252 lb.	105–124 in.	85	750K Series 3	D4K/LGP	D37EX-21/D37PX-21
650J LT/XLT/LGP	18,560–19,750 lb.	105–128 in.	99	850K Series 3	D5K/LGP	D39EX-22/D39PX-22
700J LT/XLT/LGP	26,102–28,290 lb.	120–132 in.	115	1150K	D6K/LGP	D51EX-22/D51PX-22
750J LT/WT/LGP	32,585–36,725 lb.	130–156 in.	145–155	1650K	D6N XL/LGP	D61EX-15/D61PX-15
764HSD	34,000 lb.	132 in.	200–210	—	—	—
850J LT/WT/WLT/LGP	40,165–45,375 lb.	146–168 in.	185–200	1850K	D6T XL/LGP	D65EX-15/D65PX-15
950J/LGP	56,361–59,255 lb.	145–177 in.	247	—	D7RII/LGP	D85EX-15/D85PX-15
1050J	77,843 lb.	159–170 in.	335	—	D8T	D155AX-6

CRAWLER LOADERS

DEERE	Operating Weight	Loader Bucket Capacity	Loader Dump Clearance	CAT	LIEBHERR
605C	23,600 lb.	1.7 cu. yd.	8 ft. 9 in.	939C	LR 622B and LR 632B
655C-II	33,950 lb.	2.35 cu. yd.	9 ft. 3 in.	953D	LR 622
755D	46,255 lb.	3.14 cu. yd.	9 ft. 9 in.	963D	LR 632

SCRAPER SYSTEM

SCRAPER SPECIAL TRACTORS						
DEERE	HP Range	CASE IH STEIGER SERIES			AGCO CHALLENGER MT 900C SERIES	AGCO CHALLENGER MT 800C SERIES
		Wheeled and Tracks				
9430, 9530, 9630	425–530*	385, 435, 485, 535		835, 845, 855, 865, 875		945, 955, 965, 975
CARRY-ALL AND EJECTOR SCRAPERS						
DEERE	Heaped Capacity	Total Weight	REYNOLDS	MISKIN	ASHLAND	CAT
1510C	15 cu. yd.	16,800 lb.	14CS10, 16CS10	SP-C17	—	—
1512C	15.5 cu. yd.	17,950 lb.	15CS14, 12C12	—	—	—
1512E	15.5 cu. yd.	22,100 lb.	14E10.5, 13E12	—	I-155TS2	—
1810C	18 cu. yd.	20,500 lb.	16CS10, 18CMX12.5	D-19	CS-18HD	—
1810E	18.3 cu. yd.	22,500 lb.	17E10.5	E-20	I-180TS2	TS180/TS185
1812C	18 cu. yd.	18,950 lb.	17CS12, 18CMX12.5	D-19	CS-18HD	—
1814C	18 cu. yd.	21,000 lb.	18CS14	D-26	—	—
1814E	18 cu. yd.	25,800 lb.	16E14	—	—	—
2112C	21.5 cu. yd.	25,300 lb.	—	D-26	—	—
2112E	21 cu. yd.	27,200 lb.	20E12.5	E-20	—	TS220/TS225

* = 10% power boost

SKID STEERS

DEERE	Class	Rated Operating		BOBCAT	CAT	NEW HOLLAND	CASE
		Capacity	HP Net/Gross				
313	1251-1350	1,260 lb.	45/49	S130	216B-II	L150	—
315	1351-1600	1,500 lb.	45/49	S150	226B-II	L140	410
317*	1601 < 1750	1,750 lb.	57/61	S175*	—	L170*	420
320*	1751 < 2200	1,950 lb.	62/66	S185*, S205*, S220	232B-II, 242B-II*	L175*	430, 440
325*	2201 < 2700	2,500 lb.	70/76	S250*	246C, 256C	L185*	435*, 445*, 450
328*	2701 < 3150	2,750 lb.	76/82	S300*	262C*	—	—
332*	3151 and over	3,175 lb.	85/91	S330*	272C*	L190*	465

* = vertical lift path

COMPACT TRACK LOADERS

DEERE	Class (35% of tip)	Tipping Load	HP		BOBCAT	CAT	NEW HOLLAND	CASE
			Net/Gross					
CT315	< 2000	4,400 lb.	45/49		T140	247B-II	—	—
CT322*	2100 < 2300	6,400 lb.	62/66		T180, T190*	257B-II	C175*	440CT*
CT332*	2601 and over	9,200 lb.	76/82		T320*	297C*	C190*	450CT

* = vertical lift path

ARTICULATED DUMP TRUCKS

DEERE	Rated Payload	Net Engine HP	Heaped Capacity	CAT	VOLVO	TEREX	KOMATSU
250D	51,150 lb.	265	18.0 cu. yd.	725	A25E	TA25	—
300D	60,190 lb.	285	21.7 cu. yd.	730	A30E	TA30	HM300-2
350D	71,650 lb.	380	26.3 cu. yd.	735	A35E	TA35	HM350-2
400D	81,570 lb.	413	29.4 cu. yd.	740	A40E	TA40	HM400-2

"GREEN" COMPACT UTILITY TRACTORS

DEERE	Gross Engine HP	Loader Lift Capacity	Operating Weight	KUBOTA	NEW HOLLAND	CASE/IH	CUB CADET	MASSEY
2320	24	900 lb.	1,660 lb.	B7610	TC23DA	—	5234D	—
2520	26.5	900 lb.	1,865 lb.	B2630	TC26DA	—	5264	—
2720	31.5	800 lb.	1,973 lb.	B2630	TC26DA	—	5264	—
3320	32.5	1,360 lb.	2,900 lb.	L3130, L3240	TC33DA	DX31	7530, 7532	1533
3520	37	1,360 lb.	2,900 lb.	L3430, L3540, L3940	TC34DA, TC35A/DA, TC40A/DA	DX34, DX35	8354	1540
3720	44	1,360 lb.	2,900 lb.	L3940, L4330	TC40A/DA	D40, DX40, D45, DX45	8454	—
4120	43	2,346 lb.	3,700 lb.	L4240, L4330	TC45A/DA	—	—	—
4320	48	2,346 lb.	3,700 lb.	L4630, L4740	TC48DA	D45, DX45, DX48	8454	—
4520	53	2,346 lb.	3,700 lb.	L5030, L5040, L5240	TC55DA	DX55	—	—
4720	58	2,346 lb.	3,700 lb.	L5740	TC55DA	DX55	—	—

GATOR™ UTILITY VEHICLES

DEERE	Gross Engine HP	Payload Capacity	Speed	POLARIS	KAWASAKI	KUBOTA	CUB CADET	CLUB CAR
TS 4x2	11	900 lb.	20 mph	—	—	—	—	CarryAll 252
TX 4x2	13	1,000 lb.	20 mph	Ranger 4x2	Mule 600/610	—	Cub Cadet 4x2	CarryAll 272
TH Gas 6x4	19	1,400 lb.	20 mph	Ranger 6x6	—	—	—	CarryAll 6
TH Diesel 6x4	20.8	1,600 lb.	20 mph	Ranger 6x6 EFI	Mule 4010 4x4	RTV900	—	CarryAll 295, XRT 1550
HPX Gas 4x4	20	1,400 lb.	25 mph	Ranger 500 EFI	Mule 3010 Mule 4010	RTV900 RTV1100	Cub Cadet 4x4/Trail	XRT 1550
HPX Diesel 4x4	20.8	1,400	25 mph	—	Mule 3010 4x4 Mule 4010 4x4	RTV900 RTV1100	4x4 Trail	XRT 1500
XUV 620i Gas 4x4	23	1,400 lb.	30 mph	Ranger 500 4x4 EFI/XP	Mule 3010/4010	RTV900, RTV1100	Cub Cadet 4x4 EFI	XRT 1550
XUV 850D Diesel 4x4	24.6	1,400 lb.	30 mph	—	Mule 3010 Diesel Mule 4010 Diesel	RTV900 RTV1100	Cub Cadet 4x4 Diesel	—

www.JohnDeere.com

PRODUCTIVITY • UPTIME • LOW DAILY OPERATING COSTS

Not all products sold at all dealers. Wherever applicable, specifications are in accordance with SAE standards. Models and specifications subject to change without notice. Competitive models may have changed since the publishing of this comparison.